

Specifications

Mack/International/Diamond T/ Kaiser Jeep/AM General 5 Ton 6x6 Truck "M" Series



*NOTE: This vehicle is available with four (4) different engine options. Check out which is best for you.

Engine #1

Cummins...Model NHC-250
Horsepower...250 @ 2100 RPM
Displacement...855 cu. inches
In-Line 6 Cyl. Non-Turbocharged

Transfer Case

Rockwell...Model T-138

Drive Shafts

Type...Mechanics Or Spicer

Engine #2

Model...Mack ENDT-673
Type...In-Line 6 Cyl. Turbo
Charged
Horsepower...220@ 2100 RPM
Displacement...672 cu. in.

Axles

Rockwell...Double Reduction, Full
Floating
Ratio...6.443:1

Engine #3

Hercules/Continental
Model LDS-465-1A
Horsepower...205@ 2600 RPM
In-Line 6 Cyl. Turbo Charged
Displacement...478 cu. in.

Steering

Ross Hydraulic Assisted...Model
HP-71, Model HF-64

Engine #4

Continental...Model R6602
Type...Valve in Head, 4 cyl, 6cyl
Horsepower...196 @ 2800 RPM
Displacement...602 cu. in.
Bore...4 7/8
Stroke...5 3/8
Oil Capacity...22 qts

Brake System

Standard...5 1/2" Air/ Hydraulic
Actuated
Optional...7" Air Actuated
(Tandem Only)

Clutch

Spicer...15" Single Disk

WheelBase

Short: 167"...CT 84"
Long: 179"...CT 96"
Extra-Long: 215"...CT 132"

Electrical System

24 Volt (optional 12 volt)

Tire Size

11.00 x 20 - 12 Ply...Non-
Directional

Transmission

Type...5- Speed, Manual
Spicer...6353, 5th Gear overdrive
Spicer...6352, 5th Gear Direct

Highway Speed

55 M.P.H.

Weight

Cab & Chassis...16,000 lbs.
Front Axle Rating...18,000 lbs.
Tandem Rating...44,000 lbs.