

# SPECIFICATIONS



## A. M. GENERAL M916 20 TON 6x6 TRUCK TRACTOR

### ENGINE

Cummins NTC400  
6 Cylinder Turbocharged  
400 HP @ 2,100 RPM  
Torque: 1150 ft. lb @ 1,500 RPM

### TRANSMISSION

Caterpillar.....16-Speed  
Semi-Auto Model D-7155 Overdrive  
Air control power shift

### TRANSFER CASE

Oshkosh  
Model F-U29 (18,000 series)  
Ratio 1:1 (single speed)

### TANDEM AXLES

Rockwell.....Model SUHD  
Ratio..... 6.17:1  
Rating:.....58,000 lbs.  
Differential lock up with air control

Wheelbase..... 168 inches

### STEERING AXLE

Rockwell.....Model FDS-1807  
Ratio: .....6.17 to 1  
Rating:.....20,000 lbs.

### STEERING SYSTEM

Ross.....Hydraulic Power Assist

### BRAKE SYSTEM

Rockwell S-Cam.....Full air actuated  
Rear (4) fail safe brakes

### TIRES/WHEELS

11.00R x 24.....load range G  
Budd..... 10 hole

### FIFTH WHEEL

36" (oversize kingpin)

### REAR WINCH

Hydraulic.....Rating 45,000 lbs.

### WEIGHT

Weight.....27,500 lbs.

## MEMPHIS EQUIPMENT COMPANY

The Nation's Largest Army Truck & Parts Dealer

766 South Third Street • Memphis, TN 38106 • 901/774-0600 • Fax 901/946-1919

Visit our Web Site at: [www.memphisequipment.com](http://www.memphisequipment.com)

or contact us at [info@memphisequipment.com](mailto:info@memphisequipment.com)