

SPECIFICATIONS



A. M. GENERAL M920 22.5 TON 8x6 TRUCK TRACTOR

ENGINE

Cummins NTC400 with Jake Brakes
6 Cylinder Turbocharged
400 HP @ 2,100 RPM
Torque: 1150 ft. lb @ 1,500 RPM

TRANSMISSION

Caterpillar.....16-Speed
Semi-Auto Model D-7155 Overdrive
Air control power shift

TRANSFER CASE

Oshkosh
Model F-U29 (18,000 series)
Ratio 1:1 (single speed)

TANDEM AXLES

Rockwell.....Model SUHD
Ratio..... 6.17:1
Rating:.....58,000 lbs.
Differential lock up with air control

PUSHER AXLE

Rockwell.....air operated
Rated.....20,000 lbs.

STEERING AXLE

Rockwell.....Model FDS-1807
Ratio:6.17 to 1
Rating:.....20,000 lbs.

STEERING SYSTEM

Ross.....Hydraulic Power Assist

BRAKE SYSTEM

Rockwell S-Cam.....Full air actuated
Rear (4) fail safe brakes

TIRES/WHEELS

11.00R x 24.....load range G
Budd..... 10 hole

FIFTH WHEEL

36" (oversize kingpin)

REAR WINCH

Hydraulic.....Rating 45,000 lbs.

WEIGHT

Weight.....30,200 lbs.

Wheelbase..... 211 inches

MEMPHIS EQUIPMENT COMPANY

The Nation's Largest Army Truck & Parts Dealer

766 South Third Street ▪ Memphis, TN 38106 ▪ 901/774-0600 ▪ Fax 901/946-1919

Visit our Web Site at: www.memphisequipment.com

or contact us at info@memphisequipment.com